

SensaTemp® Systems

ST 25

The ST 25 soldering system from PACE improves quality, reduce costs and eliminate the maintenance and calibration hassles associated with other soldering systems. The ST 25 maximizes heat delivery at low, safe temperatures and eliminates the need for calibration. Heavy-duty metal housing makes the system the ideal choice for the harshest production environments. The ST 25 system comes with the PS-90 Soldering Iron.

- o SensaTemp® Control Technology
- o Analog (dial) control
- o °C/°F Temperature Scales
- o Temperature Adjustment Lockout
- o ESD grounding jack
- o ESD Safe metal housing
- o Stackable
- o Can be mounted under work bench or shelf with optional bracket (1321-0509-P1)



MBT 250

Self-contained, three channel capability offers high capacity, low temperature SMT/ Thru-Hole soldering and desoldering. Digital readout displays the current channel's temperature information, error codes and programming status. Supplied with PS-90 Universal Soldering Iron, SX-100 Sodr-X-Tractor, TT-65 ThermoTweez Handpiece & TP-65 ThermoPik Handpieces.



PRC 2000

The PRC 2000 Benchtop Factory is the ultimate rework center. The PRC 2000 can tackle just about any Thru-Hole, SMT application and is well suited for multilayer repairs on damaged or prototype PCBs. Featuring 3 simultaneously active SensaTemp® handpiece channels, a built-in paste dispenser, MicroChine for removing conformal coatings or grinding away PCB laminate, and pulse heat technology. The PRC 2000 comes with 9 handpieces and continuously calibrates automatically.



Specifications	ST 25	MBT 250 SD/MBT 250 SDTP	PRC 2000 SMT	PRC 2000 TH
System 115 V	8007-0628	8007-0203 (SD) 8007-0206 (SDTP)	8007-0132	8007-0138
Power Source Only 115 V	8007-0629	8007-0349	N/A	N/A
System 230 V	8007-0610	8007-0204 (SD) 8007-0207 (SDTP)	8007-0133	N/A
Power Source Only 230 V	8007-0611	8007-0363	N/A	N/A
Input Power Requirements		97-127 VAC, 50/60 Hz or 197-263 VAC, 50/60 Hz		
Max Power Consumption	120 W	240 W		400 W
Dimensions	104mm (4.1") H x 130mm (5.1") W x 152mm (6.0") D	135mm (5.3") H x 165mm (6.5") W x 250mm (9.25") D	175mm (6.9") H x 350mm (13.75") W x 230mm (9.25") D	
Weight	2.3 Kgs (5 lbs.)	5 Kgs (11 lbs.)		13 Kgs (28.6 lbs.)
Control		LED Display		LED Display
Control Technology		SensaTemp® (Block Connector HandPieces)		
Tip to Ground Resistance		2 ohms or less		
Temperature Accuracy		Meets or exceeds ANSI-J-STD 001		
Absolute Temperature Stability		± 1.1°C (± 2 °F) at idle tip temp.		
Temperature Range		170° to 482°C (350° to 900°F) nominal		
System Can be Calibrated		Calibration not required		
Pump Type	N/A		Self Contained Pump	
Vacuum Rise Time	N/A		150 ms Average	
Vacuum (Nominal)	N/A		20 in Hg max	
Flow Control Valve	N/A		Coarse adjustment	
Pressure (Nominal)	N/A	18 p.s.i. max		7 p.s.i. max
Air Flow (Nominal)	N/A	8 slpm max		13 slpm max